EP3 coated replacement spring (right side) for model 940 and 944 doors shipped in or after July 2000.

Due to product improvements, springs of different size and finish are specified for replacement in certain doors. To verify that this is the correct replacement for your application, consider the shipment date if known, and compare the original specification on the table below to the spring that you will be replacing.

Left/Right side is as observed when standing inside the storage unit looking out at the door. In standard Trac-Rite applications, the latch side is the left side.



For 940 and 944 doors shipped in or after July 2000:

Width range: 5'1" to 9'0" Height range: Up to 10'4"

	Original Spring	Replacement Spring
Wire Diameter	.218"	.218"
Inside Diameter	3"	3"
Nominal Length	10.29"	10.29"
No. of Coils	48	46
Inch Number Per Turn (IPPT)	43	45

Corresponding left side spring is 522301

THIS DRAWING AND ALL PARTS THEREOF ARE THE EXCLUSIVE			
PROPERTY OF TRAC-RITE			
DOOR, INC. AND MAY NOT BE			
REPRODUCED IN WHOLE OR		$\sim \Gamma$	
IN PART WITHOUT WRITTEN PERMISSION.	Tra	(CII (2
I EKMISSIOIV.			
	314 Wilburn Road, Sun Prairie, WI 53590		
	Phone: 800-448-8979 Fax: 800-236-8722		
	www.tracrite.com		
DATE	DESCRIPTION		
11/21/11	SPRING, DOOR, RIGHT, 2000 -		2000 -
BY APP'D		,	2000
SJH JL	DRAWING NO.	REV.	SHEET
	522300		1 of 1
] 344300		1 ~ 1